



C\_CRSM\_CT\_IV

## Raychem CRSM CT Cable Tap Splices

### Heat-Shrink Wraparound Cable Tap Splices (1000 V)

- Use as a wraparound, sealed cable tap splice
- Qualified to ANSI C119.1 rated to ICEA electrical withstand test for 1000 volts
- RUS accepted for use with compression and split-bolt connectors
- Sealant-coated
- For use on standard poly- or elastomeric insulated conductors

#### Selection Information: dimensions in inches (millimeters)


Catalog Number	Sleeve Length	Conductor Size (1000 V max.)		Connector Dimension (Max. D)	Std. Pack
		Main (AWG/kcmil)	Tap (AWG/kcmil)		
Compression connector					
CRSM-CT-34/10-150	6 (152)	#8-#2	#10-#2	2 (51)	10
CRSM-CT-53/13-200	8 (203)	#2-4/0	#10-4/0	4 (102)	10
CRSM-CT-84/20-250	10 (254)	4/0-500	#2-500	6 (152)	10
Standard split-bolt connector					
CRSM-CT-53/13-200	8 (203)	#8-#2	#14-#2	1.5 (38)	10

#### Ordering Information

1. Select the appropriate catalog number based on the main and tap conductor sizes and connector type for electrical repair (1000 volts max.). Selections are based on typical dimensions for low-voltage insulated cable. Confirm selection with cable dimensions to assure proper sizing.
2. Kits are capable of insulating and sealing wye (3-wire) or H (4-wire) configurations up to 1000 volts.
3. Kits do not contain connectors.
4. Kits include insulating sleeve, sealant strip, and stainless steel channel closure.
5. Standard package: 10 kits/box.
6. Related test report: EDR-5192.
7. UV resistant test report: EDR-5361.

*For connector information refer to the Connectors and Terminals section of this catalog.*

Compression connector



Split-bolt connector

